

BOSTIK COLOUR SEAL

Acrylic Joint Sealant

PRODUCT

Bostik Colour Seal is a high performance acrylic gap filler and joint sealant.

DESCRIPTION

Bostik Colour Seal is a strong, highly flexible (total 20-25%), anti-fungal, mildew resistant acrylic gap filler. Colour Seal is designed for internal and external applications for horizontal and vertical sealing requirements where a flexible sealant is required. **Bostik Colour Seal** offers excellent adhesion properties when cured and is more flexible than conventional acrylic gap sealants with minimal shrinkage.

RECOMMENDED USES

- Bathroom, kitchen and laundry.
- Sealing gaps in plasterboard, brickwork, timber, concrete, cement sheet and ceramic tiles.
- May be painted with conventional available paints.
- Window and door perimeter sealing

FEATURES & BENEFITS

- Anti-fungal
- Extensive colour range available.
- Good adhesion to most building materials
- May be overpainted
- Excellent flexible properties
- Water based technology, water clean up
- Non slump
- Interior/exterior
- Australian made

TYPICAL PROPERTIES

Appearance	Smooth, paste like consistency
Colour	Various
Chemical Type	Water based acrylic
Specific Gravity	1.5
Service Temperature	-20°C to +75°C
Tack Free Working Time	15mins @ 20°C
Total Max Joint Movement	Up To 20%
Max Joint Width	25mm.

Results are after seven days cure @ 25°C and 50%RH.

PACKAGING

Bostik Colour Seal is available in 440gm cartridges in cartons of 12.

APPLICATION INSTRUCTIONS

Preparation:

Clean all surfaces by removing foreign matter and contaminants such as oil, dust, grease, frost, water, surface dirt, oil sealant and any protective coating.

Cut tip off cartridge. Cut nozzle to desired size at 45° angle. Screw nozzle onto cartridge. Place cartridge into caulking gun.

Hold gun at 45° angle with nozzle in contact with both sides of joint.

Apply by pushing sealant ahead of the nozzle, thus ensuring filler is pushed firmly into place. Remove excess filler with a wet putty knife or damp cloth. **Bostik Colour Seal** becomes touch dry within 30 minutes under ambient conditions. For best results when painting allow 72 hours prior to painting (allow longer curing time in cool or damp conditions).

PRECAUTIONS

Not recommended for use

- Where abrasion or physical abuse can be expected.
- In sealing submerged joints
- Underwater or in marine applications
- When applied to substrates below 5°C
- With absorptive surfaces such as marble, limestone or granite without prior testing for staining and/or discolouration.
- On powder coated surfaces
- On damp substrates
- On trafficable applications.
- External expansion joints
- Where joint movement is excessive (greater than 20% total joint movement).
- Where exposed to water or where water pools.

P.A.T.S (Pretested Adhesion To Substrate) Programme

Bostik offer a service in which a program has been established to eliminate potential field problems by pre-testing Bostik adhesives with samples of building materials to which the adhesive will be applied. This service is available on large projects where pre-application testing will aid in determining the proper surface preparation method to achieve optimum adhesion. Consult a Bostik representative for further information.

SAFETY DIRECTIONS

- Avoid contact with skin and eyes. If contact occurs, wash area with large quantities of water. Wear gloves for prolonged or repeated exposure.
- For more detailed information refer to Material Safety Data Sheet.

CLEAN-UP

Clean up uncured material and equipment with water immediately after using. For removal on skin, uncured sealant can be removed with Bostik Handi-Clean towels.

STORAGE

Store between 5°C and 30°C. Shelf life is a minimum of twelve months in original unopened cartridge.

FIRE

Bostik Colour Seal is non-flammable

BOSTIK COLOUR SEAL

ITEM NO.	COLOUR	STOCK SIZE
268607	Terracotta	440gm Cartridge
268593	Vanilla	440gm Cartridge
268577	White	440gm Cartridge
268615	Beige	440gm Cartridge
268623	Light Grey	440gm Cartridge
268585	Dark Grey	440gm Cartridge
269999	Black	440gm Cartridge
260007	Coffee	440gm Cartridge
285463	Chocolate Brown	440gm Cartridge

285455	Deep Green	440gm Cartridge
--------	------------	-----------------



VOC VALUE
 509 g/Ltr.
**South Coast Air Quality Mgt
 VOC Limit**
(recognised by Greenstar)
 510 g/Ltr

The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.

ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK AUSTRALIA PTY LTD

FOR FURTHER INFORMATION



BOSTIK AUSTRALIA PTY LTD
 Phone: +61-3-9279 9333
 Fax: +61-3-9279 9240

BOSTIK NZ LIMITED
 Phone: +64-4-567 5119
 Fax: +64-4-567-5412

BOSTIK SINGAPORE PTE LTD
 Phone: +65 6863 4088
 Fax: +65 6863 4077

BOSTIK (MALAYSIA) SDN BHD
 Phone: +606 764 3246
 Fax: +606 764 3248

SYDNEY
 Phone: 02 8825 3488
 Fax: 02 8825 3411

ADELAIDE
 Phone: 08 8244 0511
 Fax: 08 8244 0522

PERTH
 Phone: 08 9258 6218
 Fax: 08 9258 7687

BRISBANE
 Phone: 07 3260 2206
 Fax: 07 3260 2123

(ABN 79 003 893 838)

Product:	Colour Seal
Issue Date:	March 2002
Issue No:	2
Division:	Hardware
Total Pages:	2